

COBALT SERIES

The Cobalt series is equipped with a high-performance pressure washing system driven by a twin cylinder engine, featuring an adjustable thermostat for precision temperature control. Heating of the pressurized water is done effectively with a diesel fired heating system.

MODEL SPECIFICATIONS

FEATURES

- HONDA®, or VANGUARD® electric start V-Twin engines
- NEMA 4X electrical enclosure with burner on/off rocker switch. thermostat control, and hour meter
- 1/2" Schedule 80 coil
- Stainless steel coil cover
- Isolated pump & engine plate with vibration dampeners



FRAME

- Heavy-duty 1½ round tubular steel design
- Powder coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options
 - Dual, high volume 8.75 gallon fuel tanks
 - Total fuel capacity of 17.5 gallons (8.75 gallon gas) (8.75 gallon diesel)

INCLUDED ACCESSORIES

- Heat-resistant spray gun (up to 320° F)
- 48" Steel lance with insulated grip and 1/4" QC fitting
- 3/8" x 50' Steel-braided Armor Hose™
- High quality QC nozzles: 15°, 25°, 40° and soap
- Downstream detergent injector





MODEL SHOWN: 65002

- *Optional Accessories (sold separately and available upon order)
- 7110781- Water-separating diesel fuel filter
- 7110782- Float tank

PUMP

- Premium industrial triplex pumps; COMET or GENERAL PUMP®
- Belt drive configuration
- Axialign™ Adjustment System allows for easy belt adjustment and maintenance to be accomplished with a single bolt adjustment
- Overpressure safety relief valve
- Oversized bypass hose

DIMENSIONS					
Depth	42"				
Width	46"				
Height	38"				

MODEL #	ENGINE	PUMP	PSI	GPM	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
65001	VANGUARD® 570cc	COMET	3500	5.5	8.75 gal	8.75 gal	621 lbs
QD 65002	HONDA® GX630	GENERAL PUMP®	3500	5.5	8.75 gal	8.75 gal	626 lbs
QD 65004	HONDA® GX630	GENERAL PUMP®	4000	5.0	8.75 gal	8.75 gal	665 lbs
65005	VANGUARD® 570cc	COMET	4000	5.0	8.75 gal	8.75 gal	573 lbs
65006	VANGUARD® 570cc	GENERAL PUMP®	3500	5.5	8.75 gal	8.75 gal	573 lbs