




Eliminator™

An industrial enclosed cabinet that is designed to be easily serviced. This stationary hot water pressure washer is equipped with a natural gas or LP burner system. A 24V operating system with time delay shut off is standard on all models.

PUMP

- Premium industrial triplex pump
- Belt driven; lower RPM
- Axialign™ Adjustment System allows the alignment and high pressure pump maintenance to be easily accomplished with a single bolt adjustment
- Overpressure safety relief valve



FRAME

- Heavy-duty powder coated steel for corrosion resistance
- Vented stainless steel panels



FEATURES

- NEMA 4X electrical enclosure with rocker switch, thermostat control and hour meter
- 1/2" Schedule 80 coil piping
- Soap solenoid with metering valve
- Roll down doors and slide out tray for easy servicing
- Time delay shut down
- Remote ready wired

UNIT INCLUDES

- Pro gun handle rated 320° F
- 48" Insulated grip lance with 1/4" QC
- 3/8" x 50' Steel-braided Armor Hose™
- Stainless steel 15°, 25° and 40° QC nozzles



DIMENSIONS

Depth	30"
Width	50"
Height	53"

MODEL #	MOTOR	FUEL TYPE	PSI	GPM
65030	230V, 1Ø	Natural Gas	2000 PSI	4.0 GPM
65031	230V, 3Ø	Natural Gas	2000 PSI	4.0 GPM
65032	460V, 3Ø	Natural Gas	2000 PSI	4.0 GPM
65033	230V, 1Ø	Liquid Propane	2000 PSI	4.0 GPM
65034	230V, 3Ø	Liquid Propane	2000 PSI	4.0 GPM
65035	460V, 3Ø	Liquid Propane	2000 PSI	4.0 GPM
65036	230V, 1Ø	Natural Gas	3000 PSI	4.0 GPM
65037	230V, 3Ø	Natural Gas	3000 PSI	4.0 GPM
65038	460V, 3Ø	Natural Gas	3000 PSI	4.0 GPM
65039	230V, 1Ø	Liquid Propane	3000 PSI	4.0 GPM
65040	230V, 3Ø	Liquid Propane	3000 PSI	4.0 GPM
65041	460V, 3Ø	Liquid Propane	3000 PSI	4.0 GPM
65042	230V, 1Ø	Natural Gas	3000 PSI	5.0 GPM
65043	230V, 3Ø	Natural Gas	3000 PSI	5.0 GPM
65044	460V, 3Ø	Natural Gas	3000 PSI	5.0 GPM
65045	230V, 1Ø	Liquid Propane	3000 PSI	5.0 GPM
65046	230V, 3Ø	Liquid Propane	3000 PSI	5.0 GPM
65047	460V, 3Ø	Liquid Propane	3000 PSI	5.0 GPM
65048	230V, 3Ø	Natural Gas	3000 PSI	8.0 GPM
65049	460V, 3Ø	Natural Gas	3000 PSI	8.0 GPM
65050	230V, 3Ø	Liquid Propane	3000 PSI	8.0 GPM
65051	460V, 3Ø	Liquid Propane	3000 PSI	8.0 GPM

***Optional draft diverter** (part# 7100283), **auto start/stop shut off** (part# 7110784)
and wired NEMA 4X remote operating station available (part# 7109483)