

# Streamliner™

The Streamliner washing system can be used as a mobile, portable or stationary unit. Designed to be compact enough to fit inside a transit van or truck bed. Equipped with the optional wheel kit installed, the Streamliner fits through a 36" doorway.



## FRAME

- Heavy-duty steel base
- 1 1/2" Round tube design
- Powder coated for corrosion resistance

## PUMP

- Premium industrial triplex pump
- Direct or belt driven
- Overpressure safety relief valve

## FEATURES

### UNIT INCLUDES

- Pro gun handle rated 320° F
- 48" Insulated grip lance with 1/4" QC
- 3/8" x 50' Steel-braided Armor Hose™
- Stainless steel 15°, 25°, 40° and aluminum soap QC nozzles
- Downstream detergent injector



- NEMA 4X electrical enclosure with rocker switch, thermostat control and hour meter
- 1/2" Schedule 80 coil piping
- Electric start engine
- High temperature safety switch
- Isolated pump & engine plate with vibration dampeners

## DIMENSIONS

Depth	25"
Width	40"
Height	41"

MODEL #	ENGINE	PUMP	PSI	GPM	DRIVE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY
65016	HONDA® GX390-ES	GENERAL PUMP®	4000 PSI	4.0 GPM	Gear	5.5 gal	10 gal
65017	VANGUARD® 479cc	COMET	4000 PSI	4.0 GPM	Gear	5.5 gal	10 gal
65018	HONDA® GX390-ES	COMET	4000 PSI	4.0 GPM	Direct	5.5 gal	10 gal
65019	VANGUARD® 479cc	COMET	4000 PSI	4.0 GPM	Direct	5.5 gal	10 gal

\* Removable feet (part# 7110783) and water separating fuel filter available (part# 7110781)