

The Cobalt series is equipped with a high-performance pressure washing system driven by a twin cylinder engine, featuring an adjustable thermostat for precision temperature control. Heating of the pressurized water is done effectively with a diesel fired heating system.

MODEL SHOWN: 65002

MODEL SPECIFICATIONS

FEATURES

- V-Twin horizontal engine with electric start
- NEMA 4X electrical enclosure with burner on/off rocker switch, thermostat control and hour meter
- Corrosion resistant stainless steel coil cover
- 1/2" Schedule 80 coil
- Isolated pump & engine plate with vibration dampeners
- Total fuel capacity of 17.5 gallons (8.75 gallon gas) (8.75 gallon diesel)

FRAME

- Heavy-duty 1½ round tubular steel design
- Powder coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

PUMP

- Premium industrial triplex pumps; COMET or GENERAL PUMP®
- Belt drive configuration
- Axialign[™] adjustment system allows for easy belt adjustment and maintenance to be accomplished with a single bolt adjustment
- Oversized by pass hose

INCLUDED ACCESSORIES

- Heat-resistant spray gun (up to 320° F)
- 48" Steel lance with insulated grip and 1/4" QC fitting
- 3/8" x 50' Steel-braided Armor Hose™
- High quality QC nozzles: 15°, 25°, 40° and soap
- Downstream detergent injector

*Optional Accessories (sold separately and available upon order)

- 7110781 Water separating fuel filter
- 7110782- Float tank





DIMENSIONS						
Depth	42"					
Width	46"					
Height	38"					

MODEL #	ENGINE	PUMP	PSI	GPM	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
65001	VANGUARD® 570cc	COMET	3500	5.5	8.75 gal	8.75 gal	661 lbs
65002	HONDA® GX630	GENERAL PUMP®	3500	5.5	8.75 gal	8.75 gal	666 lbs
65004	HONDA® GX630	GENERAL PUMP®	4000	5.0	8.75 gal	8.75 gal	613 lbs
65005	VANGUARD® 570cc	COMET	4000	5.0	8.75 gal	8.75 gal	613 lbs
65006	VANGUARD® 570cc	GENERAL PUMP®	3500	5.5	8.75 gal	8.75 gal	573 lbs