



COBALT

The Cobalt is equipped with a high-performance pressure washing system driven by a twin cylinder engine, featuring an adjustable thermostat for precision temperature control. Heating of the pressurized water is done effectively with a diesel fired heating system.

MODEL SPECIFICATIONS

FEATURES

- NEMA 4X electrical enclosure with rocker switch, thermostat control, and hour meter
- 1/2" Schedule 80 coil piping
- Electric start V-twin engines
- Stainless steel coil cover
- Isolated pump & engine plate with vibration dampeners



MODEL SHOWN: 65002

FRAME

- Heavy-duty steel frame
- Powder coated for corrosion resistance
- 1 1/2" Round tube design
- Removable feet for forklift capabilities and alternative mounting options

INCLUDED ACCESSORIES

- Heat-resistant spray gun (up to 320° F)
- 48" lance with insulated grip and 1/4" QC
- 3/8" x 50' Steel-braided Armor Hose™
- High quality QC nozzles 15°, 25°, 40° and soap
- Downstream detergent injector



PUMP

- Premium industrial triplex pump
- Belt drive
- Axialign™ Adjustment System allows for easy belt adjustment and maintenance to be easily accomplished with a single bolt adjustment
- Overpressure safety relief valve

DIMENSIONS

Depth	41 3/4"
Width	45 1/4"
Height	37 1/8"

* Optional Accessories (sold separately)

- 7110781- Water-separating diesel fuel filter
- 7110782- Float Tank

MODEL #	ENGINE	PUMP	PSI	GPM	GAS TANK	DIESEL TANK
** QD 65001	VANGUARD® 570cc	COMET	3500	5.5	8.75 gal	8.75 gal
** QD 65002	HONDA® GX630	GENERAL PUMP®	3500	5.5	8.75 gal	8.75 gal
65003	KOHLER® CH620	COMET	3500	5.5	8.75 gal	8.75 gal
** QD 65004	HONDA® GX630	GENERAL PUMP®	4000	5.0	8.75 gal	8.75 gal
65005	VANGUARD® 570cc	COMET	4000	5.0	8.75 gal	8.75 gal
65006	VANGUARD® 570cc	GENERAL PUMP®	3500	5.5	8.75 gal	8.75 gal

** Quick delivery product