

Equalizer

The Equalizer is available in gas and electric models for a variety of cleaning applications. This full featured vertical coil pressure washing system is equipped with a wide four-wheel stance that does not compromise mobility or versatility.

FRAME

- Heavy-duty steel frame
- 11/2" Round tube design
- Powder coated for corrosion resistance
- Four-wheel easy mobility





• Industrial triplex pump

Delco

unland

• Direct or belt driven

UNIT INCLUDES

- Pro gun handle rated 320° F
- 36" Insulated grip lance with 1/4" QC
- 3/8" x 50' Steel-braided Armor Hose™
- Stainless steel 0°, 15°, 25° and 40° QC nozzles



- NEMA 4X electrical enclosure with rocker switch, thermostat control and hour meter
- Large capacity diesel fuel tank
- Vertical heat exchanger
- Stainless steel float tank (on electric model)

FEATURES

- Electric direct, electric belt and gas driven models available
- 35' GFCI electrical cord
- Tires designed with chevron treading for increased vibration dampening and stabilization
- Wheel Brake

3000 PSI

3000 PSI

DIMENSIONS				
Depth	43"			
Width	30″			
Height	35"			

HONDA® GX390

HONDA® GX390

Direct

Direct

MODEL#	DESCRIPTION	PSI	GPM	PUMP	DRIVE	VOLTAGE/ PHASE
65060	EQUALIZER 1030E1	1000 PSI	3.0 GPM	COMET	Direct	120V 1Ø
65061	EQUALIZER 1030E2	1000 PSI	3.0 GPM	COMET	Direct	230V 1Ø
65063	EQUALIZER 2040E2	2000 PSI	4.0 GPM	COMET	Belt	230V 1Ø
MODEL#	DESCRIPTION	PSI	GPM	PUMP	DRIVE	VOLTAGE
65062	EQUALIZER 2040E2	2000 PSI	4.0 GPM	COMET	Direct	230V 1Ø
65064	EQUALIZER 2040E3	2000 PSI	4.0 GPM	COMET	Belt	230V 3Ø
65065	EQUALIZER 3040E2	3000 PSI	4.0 GPM	COMET	Belt	230V 1Ø
65066	EQUALIZER 3040E3	3000 PSI	4.0 GPM	COMET	Belt	230V 3Ø
MODEL#	DESCRIPTION	PSI GP	M	PUMP	DRIVE	ENGINE

4.0 GPM

4.0 GPM

COMET

GENERAL PUMP®

EQUALIZER 3040HC

EQUALIZER 3040HG

65068

65069